




H07V-U, H07V-R



Cabluri monofilare fara manta cu izolatie din PVC

Unsheathed single-core PVC-insulated cables



Standard de fabricatie: EN 50525-2-31;
Tensiune nominala U_0/U : 0.45/0.75 kV

Reference standard: EN 50525-2-31
Rated voltage U_0/U : 0.45/0.75 kV

Domeniul de utilizare

Cablurile sunt utilizate pentru instalatii electrice fixe, interioare la tensiune de 450/750 V. Se pot instala in conducte la vedere sau nu, direct sub tencuiala, in medii uscate sau umede.

Applications

Indoor wirings at voltages up to 450/750 V. They can be installed in open or buried conduits, directly under drywall, in dry or moist environments.

Temperatura max. de lucru in functionarea de durata: +70°C

Max. long-run operational temperature: +70°C

Temperatura minima a cablului (masurata pe manta):

Min. cable temperature (masured on the sheath surface)

- **la montaj:** +5°C
- **in exploatare:** -10°C

- **during installation:** +5°C
- **in operation:** -10°C

Temperatura max. in scurtcircuit (max 5 sec): +160°C

Max. temperature during short circuit (max. 5 seconds): +160°C

Conductor de cupru

Conductor de cupru recopt unifilar rigid (re) sau multifilar rigid (rm); SR EN 60228

Conductor de cupru

Solid conductor (re), or concentrically stranded conductor (rm); SR EN 60228

Izolatie

PVC tip TI2.

Conductoarele izolate sunt cu intarziere la propagarea flacarii conf. SR EN 60332-1-2; Certificare conf. SR EN 50575 – clasa Eca;

Insulation

PVC, TI2 type.

Flame retardant cables, test according to SR EN 60332-1-2; SR EN 50525 certified – Eca class

Marcaj

SC ELECTROPLAST SA, simbol cablu, tensiune de lucru, an de fabricatie, **Eca**

Marking

SC ELECTROPLAST SA, cable symbol, operational voltage, manufacture year, **Eca**.

Raza minima de curbura

6 x diametru cablului

Min. bending radius

6 x cable diameter

Cod de culori

- Cabluri monoculare: negru, albastru, maro, gri, portocaliu, roz, rosu, turcoaz, violet, alb.
- Cabluri biculare: galben-verde, min 30% verde, max 70% galben

Color coding

- Monochrome cables: black, blue, brown, gray, orange, pink, red, cyan, violet, white
- Yellow-green cables: min 30% green, max 70% yellow.

*Alte combinatii biculare nu sunt permise

*Other two-color combinations are not allowed.

H07V-U, H07V-R



Cabluri monofilare fara manta cu izolatie din PVC

Unsheathed single-core PVC-insulated cables

Simbol	Sectiune nominala a conductorului	Tip cond.	Diametru exterior nominal	Rezistenta electrica, max la 20°C	Rezistenta de izolatie la 70°C, min	Masa Inf
<i>Symbol</i>	<i>Nominal cross-section of conductor</i>	<i>Type of cond</i>	<i>Nominal outer diameter</i>	<i>Max. resistance at 20°C</i>	<i>Min. insulation resistance at 70°C</i>	<i>Mass inf</i>
	mm ²		mm	Ω/km	MΩ*km	kg/km
H07V-U	1.5	re	2.6-3.2	12.1	0.011	20
	2.5	re	3.2-3.9	7.41	0.010	31
	4	re	3.6-4.4	4.61	0.0087	45
	6	re	4.1-5.0	3.08	0.0074	65
H07V-U	10	re	5.3-6.4	1.83	0.0072	108
H07V-R	10	rm	5.6-6.7	1.83	0.0067	111
	16	rm	6.4-7.8	1.15	0.0056	164
	25	rm	8.1-9.7	0.727	0.0053	255
	35	rm	9.0-10.9	0.524	0.0046	343
	50	rm	10.6-12.8	0.387	0.0046	471
	70	rm	12.1-14.6	0.268	0.0040	663
	95	rm	14.1-17.1	0.193	0.0039	913
	120	rm	15.6-18.8	0.153	0.0035	1125
	150	rm	17.3-20.9	0.124	0.0035	1371
	185	rm	19.3-23.3	0.0991	0.0035	1752
	240	rm	22.0-26.6	0.0754	0.0034	2265
300	rm	24.5-29.6	0.0601	0.0033	2843	